

BASE OILS

SN New Base Oils Group I

PRODUCT CODE	ASTM Color, (ASTM D 1500)	Density at 15°C, Kg/m ³ (ASTM D 1298)	Flash Point COC, °C (ASTM D 92)	Pour Point, °C (ASTM D 97)	Viscosity at 40°C, cSt (ASTM D445)	Viscosity at 100°C, cSt (ASTM D445)	Viscosity Index, (ASTM D 2270)	Total Sulphur, %wt (ASTM D 2622)
	Typical	Typical	Typical	Typical	Typical	Typical	Typical	Typical
SN 90	L 0,5	857	210	-9	15,7	3,5	100	0,3
SN 150	0,5	874	220	-9	31,3	5,3	100	0,3
SN 500	L 1,5	888	240	-9	92,0	10,5	96	0,4
BS 150	4,0	905	290	-6	460,0	30,5	95	0,9

CN New Base Oils Group II

PRODUCT CODE	ASTM Color, (ASTM D 1500)	Density at 15°C, Kg/m ³ (ASTM D 1298)	Flash Point COC, °C (ASTM D 92)	Pour Point, °C (ASTM D 97)	Viscosity at 40°C, cSt (ASTM D445)	Viscosity at 100°C, cSt (ASTM D445)	Viscosity Index, (ASTM D 2270)	Total Sulphur, %wt (ASTM D 2622)
	Typical	Typical	Typical	Typical	Typical	Typical	Typical	Typical
CN 70	+30	857	180	-24	12,0	2,9	85	<10
CN 80	+30	861	180	-24	13,9	3,1	77	<10
CN 110	+30	854	210	-18	21,0	4,2	100	<10
CN 225	+30	866	224	-15	42,5	6,4	100	<10
CN 600	+28	872	260	-15	110,0	12,1	100	<10

⬡ HN New Base Oils Group III

PRODUCT CODE	Saybolt Color, (ASTM D 156)	Density AT 15°C, Kg/m ³ (ASTM D 1298)	Flash Point COC, °C (ASTM D 92)	Pour Point, °C (ASTM D 97)	Viscosity at 40°C, cSt (ASTM D445)	Viscosity at 100°C, cSt (ASTM D445)	Viscosity Index, (ASTM D 2270)	Total Sulphu, ppm (ASTM D 2622)	Noack Volatility, %p (ASTM D 5800)
	Typical	Typical	Typical	Typical	Typical	Typical	Typical	Typical	Typical
HN 4	+30	833	220	-20	19,0	4,2	127	<50	14
HN 6	+30	843	240	-18	35,0	6,2	126	<50	7

Due to continual product research and development, the information contained herein is subject to change without notification