

⬡ LBR Regenerated Base Oils Group I

| PRODUCT CODE | ASTM Color, (ASTM D 1500) | Density at 15°C, Kg/m ³ (ASTM D 1298) | Flash Point COC, °C (ASTM D 92) | Pour point, °C (ASTM D 97) | Viscosity at 40°C, cSt (ASTM D445) | Viscosity at 100°C, Cst (ASTM D445) | Viscosity Index, (ASTM D 2270) | Total Sulphur, %w (ASTM D 2622) | Neutralization N, MgKOH/g (ASTM D 974) |
|--------------|------------------------------|---|------------------------------------|-------------------------------|---------------------------------------|--|-----------------------------------|------------------------------------|---|
| | Typical | Typical | Typical | Typical | Typical | Typical | Typical | Typical | Typical |
| LBR 2-R | L 1,5 | 856 | 200 | -9 | 20 | 4,1 | 105 | 0,4 | 0,02 |
| LBR 3-R | 1,5 | 859 | 210 | -6 | 29 | 5,2 | 110 | 0,3 | 0,02 |
| LBR 5-R | L 3,0 | 872 | 224 | -6 | 56 | 8,0 | 110 | 0,4 | 0,02 |
| LBR 8-R | L 3,5 | 879 | 228 | -6 | 88 | 10,8 | 107 | 0,5 | 0,02 |

Due to continual product research and development, the information contained herein is subject to change without notification